
Cawdrey

Release 0.2.0

Dominic Davis-Foster

Sep 25, 2020

CONTENTS

1	Contents	3
2	Other Dictionary Packages	5
3	Installation	7
3.1	AlphaDict	7
3.2	bdict	9
3.3	frozendict	11
3.4	FrozenOrderedDict	16
3.5	NonelessDict	19
3.6	Base Classes	24
3.7	Functions	29
3.8	Overview	29
3.9	Coding style	30
3.10	Automated tests	30
3.11	Type Annotations	30
3.12	Build documentation locally	30
3.13	Downloading source code	30
4	And Finally:	33
	Python Module Index	35
	Index	37

Several useful custom dictionaries for Python

Docs	
Tests	
PyPI	
Anaconda	
Activity	
Other	

CONTENTS

- `frozendict`: An immutable dictionary that cannot be changed after creation.
- `FrozenOrderedDict`: An immutable `OrderedDict` where the order of keys is preserved, but that cannot be changed after creation.
- `AlphaDict`: A `FrozenOrderedDict` where the keys are stored in alphabetical order.
- `bdict`: A dictionary where *key*, *value* pairs are stored both ways round.

This package also provides two base classes for creating your own custom dictionaries:

- `FrozenBase`: An Abstract Base Class for Frozen dictionaries.
- `MutableBase`: An Abstract Base Class for mutable dictionaries.

OTHER DICTIONARY PACKAGES

If you're looking to unflatten a dictionary, such as to go from this:

```
{'foo.bar': 'val'}
```

to this:

```
{'foo': {'bar': 'val'}}
```

check out [unflatten](#), [flattery](#) or [morph](#) to accomplish that.

[indexed](#) provides an `OrderedDict` where the values can be accessed by their index as well as by their keys.

There's also [python-benedict](#), which provides a custom dictionary with **keylist/keypath** support, **I/O** shortcuts (Base64, CSV, JSON, TOML, XML, YAML, pickle, query-string) and many **utilities**.

INSTALLATION

from PyPI

```
$ python3 -m pip install cawdrey --user
```

from Anaconda

First add the required channels

```
$ conda config --add channels https://conda.anaconda.org/domdfcoding  
$ conda config --add channels https://conda.anaconda.org/conda-forge
```

Then install

```
$ conda install cawdrey
```

from GitHub

```
$ python3 -m pip install git+https://github.com/domdfcoding/cawdrey@master --user
```

3.1 AlphaDict

class AlphaDict (*seq=None, **kwargs*)

Bases: `cawdrey.frozenorderreddict.FrozenOrderedDict`

Initialize an immutable, alphabetised dictionary.

The signature is the same as regular dictionaries.

`AlphaDict()` -> new empty `AlphaDict`

`AlphaDict(mapping)` -> new `AlphaDict` initialized from a mapping object's (key, value) pairs

`AlphaDict(iterable)` -> new `AlphaDict` initialized as if via:

```
d = {}  
for k, v in iterable:  
    d[k] = v
```

`AlphaDict(**kwargs)` -> new `AlphaDict` initialized with the `name=value` pairs in the keyword argument list.

For example:

```
AlphaDict(one=1, two=2)
```

Methods:

<code>__contains__(key)</code>	Return key in self.
<code>__eq__(other)</code>	Return self == other.
<code>__getitem__(key)</code>	Return self[key].
<code>__iter__()</code>	Iterates over the dictionary's keys
<code>__len__()</code>	Returns the number of keys in the dictionary.
<code>__repr__()</code>	Return a string representation of the <i>DictWrapper</i> .
<code>copy(*args, **kwargs)</code>	Return a copy of the <i>FrozenOrderedDict</i> .
<code>fromkeys(iterable[, value])</code>	Create a new dictionary with keys from iterable and values set to value.
<code>get(k[, default])</code>	Return the value for k if k is in the dictionary, else default.
<code>items()</code>	Returns a set-like object providing a view on the <i>FrozenOrderedDict</i> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <i>FrozenOrderedDict</i> 's keys.
<code>values()</code>	Returns an object providing a view on the <i>FrozenOrderedDict</i> 's values.

`__contains__(key)`

Return key in self.

Parameters `key` (object)

Return type `bool`

`__eq__(other)`

Return self == other.

Return type `bool`

`__getitem__(key)`

Return self[key].

Parameters `key` (~KT)

Return type ~VT

`__iter__()`

Iterates over the dictionary's keys

Return type `Iterator[~KT]`

`__len__()`

Returns the number of keys in the dictionary.

Return type `int`

`__repr__()`

Return a string representation of the *DictWrapper*.

Return type `str`

`copy(*args, **kwargs)`

Return a copy of the *FrozenOrderedDict*.

Parameters

- **args**
- **kwargs**

classmethod fromkeys (*iterable, value=None*)

Create a new dictionary with keys from iterable and values set to value.

get (*k, default=None*)

Return the value for k if k is in the dictionary, else default.

Parameters

- **k** – The key to return the value for.
- **default** – The value to return if key is not in the dictionary. Default `None`.

items ()

Returns a set-like object providing a view on the `FrozenOrderedDict`'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

keys ()

Returns a set-like object providing a view on the `FrozenOrderedDict`'s keys.

Return type `AbstractSet[~KT]`

values ()

Returns an object providing a view on the `FrozenOrderedDict`'s values.

Return type `ValuesView[~VT]`

3.2 bdict

class bdict (*seq=None, **kwargs*)

Bases: `collections.UserDict`

Returns a new dictionary initialized from an optional positional argument, and a possibly empty set of keyword arguments.

Each `key: value` pair is entered into the dictionary in both directions, so you can perform lookups with either the key or the value.

If no positional argument is given, an empty dictionary is created.

If a positional argument is given and it is a mapping object, a dictionary is created with the same key-value pairs as the mapping object. Otherwise, the positional argument must be an iterable object. Each item in the iterable must itself be an iterable with exactly two objects. The first object of each item becomes a key in the new dictionary, and the second object the corresponding value.

If keyword arguments are given, the keyword arguments and their values are added to the dictionary created from the positional argument.

If an attempt is made to add a key or value that already exists in the dictionary a `ValueError` will be raised.

Keys or values of `None`, `True` and `False` will be stored internally as `"_None"`, `"_True"` and `"_False"` respectively

Based on <https://stackoverflow.com/a/1063393> by <https://stackoverflow.com/users/9493/brian>

Improved May 2020 with suggestions from <https://treyhunner.com/2019/04/why-you-shouldnt-inherit-from-list-and-dict-in-python/>

Methods:

<code>__contains__(key)</code>	Return key in self.
<code>__delitem__(key)</code>	Delete self[key].
<code>__eq__(other)</code>	Return self == other.
<code>__getitem__(key)</code>	Return self[key].
<code>__repr__()</code>	Return repr(self).
<code>__setitem__(key, val)</code>	Set self[key] to value.
<code>clear()</code>	Removes all items from the <i>bdict</i> .
<code>get()</code>	Return the value for k if k is in the dictionary, else default.
<code>items()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's keys.
<code>pop(k[,d])</code>	If key is not found, d is returned if given, otherwise KeyError is raised.
<code>popitem()</code>	as a 2-tuple; but raise KeyError if D is empty.
<code>setdefault(k[,d])</code>	
<code>update([E,]**F)</code>	If E present and has a .keys() method, does: for k in E: D[k] = E[k] If E present and lacks .keys() method, does: for (k, v) in E: D[k] = v In either case, this is followed by: for k, v in F.items(): D[k] = v
<code>values()</code>	Returns an object providing a view on the <i>bdict</i> 's values.

`__contains__(key)`

Return key in self.

Parameters `key` (object)

Return type `bool`

`__delitem__(key)`

Delete self[key].

Parameters `key` (~KT)

`__eq__(other)`

Return self == other.

Return type `bool`

`__getitem__(key)`

Return self[key].

Parameters `key` (~KT)

Return type ~VT

`__repr__()`

Return repr(self).

`__setitem__(key, val)`

Set self[key] to value.

Parameters

• `key`

- **val**

clear()
Removes all items from the *bdict*.

Return type `None`

get (*k*: *KT*) → `Optional[VT]`
get (*k*: *KT*, *default*: `Union[VT, T]`) → `Union[VT, T]`
 Return the value for *k* if *k* is in the dictionary, else *default*.

Parameters

- **k** – The key to return the value for.
- **default** – The value to return if *key* is not in the dictionary. Default `None`.

items()
Returns a set-like object providing a view on the *bdict*'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

keys()
Returns a set-like object providing a view on the *bdict*'s keys.

Return type `AbstractSet[~KT]`

pop (*k*[, *d*]) → *v*, remove specified key and return the corresponding value.
 If key is not found, *d* is returned if given, otherwise `KeyError` is raised.

popitem() → (*k*, *v*), remove and return some (key, value) pair
 as a 2-tuple; but raise `KeyError` if *D* is empty.

setdefault (*k*[, *d*]) → *D.get(k,d)*, also set *D*[*k*]=*d* if *k* not in *D*

update (*E*, ***F*) → `None`. Update *D* from mapping/iterable *E* and *F*.
 If *E* present and has a `.keys()` method, does: for *k* in *E*: *D*[*k*] = *E*[*k*] If *E* present and lacks `.keys()` method,
 does: for (*k*, *v*) in *E*: *D*[*k*] = *v* In either case, this is followed by: for *k*, *v* in *F.items*(): *D*[*k*] = *v*

values()
Returns an object providing a view on the *bdict*'s values.

Return type `ValuesView[~VT]`

3.3 frozendict

3.3.1 About

frozendict is an immutable wrapper around dictionaries that implements the complete mapping interface. It can be used as a drop-in replacement for dictionaries where immutability is desired.

Of course, this is `python`, and you can still poke around the object's internals if you want.

The *frozendict* constructor mimics `dict`, and all of the expected interfaces (`iter`, `len`, `repr`, `hash`, `getitem`) are provided. Note that a *frozendict* does not guarantee the immutability of its values, so the utility of the `hash` method is restricted by usage.

The only difference is that the `copy()` method of *frozendict* takes variable keyword arguments, which will be present as key/value pairs in the new, immutable copy.

3.3.2 Usage

```
>>> from cawdrey import frozendict
>>>
>>> fd = frozendict({'hello': 'World' })
>>>
>>> print fd
<frozendict {'hello': 'World'}>
>>>
>>> print fd['hello']
'World'
>>>
>>> print fd.copy(another='key/value')
<frozendict {'hello': 'World', 'another': 'key/value'}>
>>>
```

In addition, *frozendict* supports the + and - operands. If you add a *dict*-like object, a new *frozendict* will be returned, equal to the old *frozendict* updated with the other object. Example:

```
>>> frozendict({"Sulla": "Marco", 2: 3}) + {"Sulla": "Marò", 4: 7}
<frozendict {'Sulla': 'Marò', 2: 3, 4: 7}>
>>>
```

You can also subtract an iterable from a *frozendict*. A new *frozendict* will be returned, without the keys that are in the iterable. Examples:

```
>>> frozendict({"Sulla": "Marco", 2: 3}) - {"Sulla": "Marò", 4: 7}
<frozendict {'Sulla': 'Marco', 2: 3}>
>>> frozendict({"Sulla": "Marco", 2: 3}) - [2, 4]
<frozendict {'Sulla': 'Marco'}>
>>>
```

Some other examples:

```
>>> from cawdrey import frozendict
>>> fd = frozendict({"Sulla": "Marco", "Hicks": "Bill"})
>>> print(fd)
<frozendict {'Sulla': 'Marco', 'Hicks': 'Bill'}>
>>> print(fd["Sulla"])
Marco
>>> fd["Bim"]
KeyError: 'Bim'
>>> len(fd)
2
>>> "Sulla" in fd
True
>>> "Sulla" not in fd
False
>>> "Bim" in fd
False
>>> hash(fd)
835910019049608535
>>> fd_unhashable = frozendict({1: []})
>>> hash(fd_unhashable)
TypeError: unhashable type: 'list'
>>> fd2 = frozendict({"Hicks": "Bill", "Sulla": "Marco"})
>>> print(fd2)
```

(continues on next page)

(continued from previous page)

```

<frozendict {'Hicks': 'Bill', 'Sulla': 'Marco'}>
>>> fd2 is fd
False
>>> fd2 == fd
True
>>> frozendict()
<frozendict {}>
>>> frozendict(Sulla="Marco", Hicks="Bill")
<frozendict {'Sulla': 'Marco', 'Hicks': 'Bill'}>
>>> frozendict(("Sulla", "Marco"), ("Hicks", "Bill"))
<frozendict {'Sulla': 'Marco', 'Hicks': 'Bill'}>
>>> fd.get("Sulla")
'Marco'
>>> print(fd.get("God"))
None
>>> tuple(fd.keys())
('Sulla', 'Hicks')
>>> tuple(fd.values())
('Marco', 'Bill')
>>> tuple(fd.items())
(('Sulla', 'Marco'), ('Hicks', 'Bill'))
>>> iter(fd)
<dict_keyiterator object at 0x7feb75c49188>
>>> frozendict.fromkeys(["Marco", "Giulia"], "Sulla")
<frozendict {'Marco': 'Sulla', 'Giulia': 'Sulla'}>
>>> fd["Sulla"] = "Silla"
TypeError: 'frozendict' object does not support item assignment
>>> del fd["Sulla"]
TypeError: 'frozendict' object does not support item deletion
>>> fd.clear()
AttributeError: 'frozendict' object has no attribute 'clear'
>>> fd.pop("Sulla")
AttributeError: 'frozendict' object has no attribute 'pop'
>>> fd.popitem()
AttributeError: 'frozendict' object has no attribute 'popitem'
>>> fd.setdefault("Sulla")
AttributeError: 'frozendict' object has no attribute 'setdefault'
>>> fd.update({"Bim": "James May"})
AttributeError: 'frozendict' object has no attribute 'update'

```

3.3.3 API Reference

class frozendict (*args, **kwds)

Bases: *cawdrey.base.FrozenBase*

An immutable wrapper around dictionaries that implements the complete `collections.Mapping` interface. It can be used as a drop-in replacement for dictionaries where immutability is desired.

Methods:

`__add__`(other, *args, **kwargs)

If you add a dict-like object, a new frozendict will be returned, equal to the old frozendict updated with the other object.

continues on next page

Table 3 – continued from previous page

<code>__and__(other, *args, **kwargs)</code>	Returns a new <i>frozendict</i> , that is the intersection between <i>self</i> and <i>other</i> .
<code>__contains__(key)</code>	Return <i>key</i> in <i>self</i> .
<code>__eq__(other)</code>	Return <i>self</i> == <i>other</i> .
<code>__getitem__(key)</code>	Return <i>self</i> [<i>key</i>].
<code>__iter__()</code>	Iterates over the dictionary's keys
<code>__len__()</code>	Returns the number of keys in the dictionary.
<code>__repr__()</code>	Return a string representation of the <i>DictWrapper</i> .
<code>__sub__(other, *args, **kwargs)</code>	The method will create a new <i>frozendict</i> , result of the subtraction by <i>other</i> .
<code>fromkeys(iterable[, value])</code>	Create a new dictionary with keys from <i>iterable</i> and values set to <i>value</i> .
<code>get(k[, default])</code>	Return the value for <i>k</i> if <i>k</i> is in the dictionary, else <i>default</i> .
<code>items()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's keys.
<code>sorted(*args[, by])</code>	Return a new <i>frozendict</i> , with the element insertion sorted.
<code>values()</code>	Returns an object providing a view on the <i>bdict</i> 's values.

`__add__(other, *args, **kwargs)`

If you add a dict-like object, a new *frozendict* will be returned, equal to the old *frozendict* updated with the other object.

`__and__(other, *args, **kwargs)`

Returns a new *frozendict*, that is the intersection between *self* and *other*.

If *other* is a *dict*-like object, the intersection will contain only the *items* in common.

If *other* is another iterable, the intersection will contain the items of *self* which keys are in *other*.

Iterables of pairs are *not* managed differently. This is for consistency.

Beware! The final order is dictated by the order of *other*. This allows the coder to change the order of the original *frozendict*.

The last two behaviours breaks voluntarily the `dict.items()` API, for consistency and practical reasons.

`__contains__(key)`

Return *key* in *self*.

Parameters *key* (object)

Return type *bool*

`__eq__(other)`

Return *self* == *other*.

Return type *bool*

`__getitem__(key)`

Return *self*[*key*].

Parameters *key* (~KT)

Return type ~VT

`__iter__()`

Iterates over the dictionary's keys

Return type `Iterator[~KT]`

`__len__()`

Returns the number of keys in the dictionary.

Return type `int`

`__repr__()`

Return a string representation of the `DictWrapper`.

Return type `str`

`__sub__(other, *args, **kwargs)`

The method will create a new `frozendict`, result of the subtraction by `other`.

If `other` is a dict-like, the result will have the items of the `frozendict` that are *not* in common with `other`.

If `other` is another type of iterable, the result will have the items of `frozendict` without the keys that are in `other`.

classmethod `fromkeys(iterable, value=None)`

Create a new dictionary with keys from iterable and values set to value.

get (`k, default=None`)

Return the value for `k` if `k` is in the dictionary, else `default`.

Parameters

- `k` – The key to return the value for.
- `default` – The value to return if `key` is not in the dictionary. Default `None`.

items ()

Returns a set-like object providing a view on the `bdict`'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

keys ()

Returns a set-like object providing a view on the `bdict`'s keys.

Return type `AbstractSet[~KT]`

sorted (`*args, by='keys', **kwargs`)

Return a new `frozendict`, with the element insertion sorted. The signature is the same as the builtin `sorted` function, except for the additional parameter `by`, that is "keys" by default and can also be "values" and "items". So the resulting `frozendict` can be sorted by keys, values or items.

If you want more complicated sorts read the documentation of `sorted`.

The the parameters passed to the `key` function are the keys of the `frozendict` if `by = "keys"`, and are the items otherwise.

Note: Sorting by keys and items achieves the same effect. The only difference is when you want to customize the sorting passing a custom `key` function. You *could* achieve the same result using `by = "values"`, since also sorting by values passes the items to the `key` function. But this is an implementation detail and you should not rely on it.

`values()`

Returns an object providing a view on the *bdict*'s values.

Return type `ValuesView[~VT]`

3.3.4 Copyright

Based on <https://github.com/slezica/python-frozendict> and <https://github.com/mredolatti/python-frozendict>.

Copyright (c) 2012 Santiago Lezica

Licensed under the MIT License:

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Also based on <https://github.com/Marco-Sulla/python-frozendict>

Copyright (c) Marco Sulla

Licensed under the [GNU Lesser General Public License Version 3](#)

3.4 FrozenOrderedDict

3.4.1 About

FrozenOrderedDict is a immutable wrapper around an *OrderedDict*.

FrozenOrderedDict is similar to *frozendict*, and with regards to immutability it solves the same problems:

- Because dictionaries are mutable, they are not hashable and cannot be used in sets or as dictionary keys.
- Nasty bugs can and do occur when mutable data structures are passed around.

It can be initialized just like a *dict* or *OrderedDict*. Once instantiated, an instance of *FrozenOrderedDict* cannot be altered, since it does not implement the *MutableMapping* interface.

It does implement the *Mapping* interface, so can be used just like a normal dictionary in most cases.

In order to modify the contents of a *FrozenOrderedDict*, a new instance must be created. The easiest way to do that is by calling the *.copy()* method. It will return a new instance of *FrozenOrderedDict* initialized using the following steps:

1. A copy of the wrapped *OrderedDict* instance will be created.

2. If any arguments or keyword arguments are passed to the `.copy()` method, they will be used to create another `OrderedDict` instance, which will then be used to update the copy made in step #1.
3. Finally, `self.__class__()` will be called, passing the copy as the only argument.

3.4.2 API Reference

class FrozenOrderedDict (*args, **kwds)

Bases: `cawdrey.base.FrozenBase`

An immutable `OrderedDict`. It can be used as a drop-in replacement for dictionaries where immutability is desired.

Methods:

<code>__contains__(key)</code>	Return key in self.
<code>__eq__(other)</code>	Return self == other.
<code>__getitem__(key)</code>	Return self[key].
<code>__iter__()</code>	Iterates over the dictionary's keys
<code>__len__()</code>	Returns the number of keys in the dictionary.
<code>__repr__()</code>	Return a string representation of the <code>DictWrapper</code> .
<code>copy(*args, **kwargs)</code>	Return a copy of the <code>FrozenOrderedDict</code> .
<code>fromkeys(iterable[, value])</code>	Create a new dictionary with keys from iterable and values set to value.
<code>get()</code>	Return the value for k if k is in the dictionary, else default.
<code>items()</code>	Returns a set-like object providing a view on the <code>FrozenOrderedDict</code> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <code>FrozenOrderedDict</code> 's keys.
<code>values()</code>	Returns an object providing a view on the <code>FrozenOrderedDict</code> 's values.

`__contains__(key)`

Return key in self.

Parameters `key` (object)

Return type `bool`

`__eq__(other)`

Return self == other.

Return type `bool`

`__getitem__(key)`

Return self[key].

Parameters `key` (~KT)

Return type ~VT

`__iter__()`

Iterates over the dictionary's keys

Return type `Iterator[~KT]`

`__len__()`

Returns the number of keys in the dictionary.

Return type `int`

`__repr__()`

Return a string representation of the `DictWrapper`.

Return type `str`

`copy(*args, **kwargs)`

Return a copy of the `FrozenOrderedDict`.

Parameters

- `args`
- `kwargs`

classmethod `fromkeys(iterable, value=None)`

Create a new dictionary with keys from iterable and values set to value.

get (`k: KT`) → `Optional[VT]`

get (`k: KT, default: Union[VT, T]`) → `Union[VT, T]`

Return the value for `k` if `k` is in the dictionary, else `default`.

Parameters

- `k` – The key to return the value for.
- `default` – The value to return if `key` is not in the dictionary. Default `None`.

`items()`

Returns a set-like object providing a view on the `FrozenOrderedDict`'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

`keys()`

Returns a set-like object providing a view on the `FrozenOrderedDict`'s keys.

Return type `AbstractSet[~KT]`

`values()`

Returns an object providing a view on the `FrozenOrderedDict`'s values.

Return type `ValuesView[~VT]`

3.4.3 Copyright

Based on <https://github.com/slezica/python-frozendict> and <https://github.com/mredolatti/python-frozendict> .

Copyright (c) 2012 Santiago Lezica

Licensed under the MIT License:

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Also based on <https://github.com/Marco-Sulla/python-frozendict>
Copyright (c) Marco Sulla
Licensed under the GNU Lesser General Public License Version 3

Also based on <https://github.com/wsmith323/frozenorderreddict>
Copyright (c) 2015 Warren Smith
Licensed under the MIT License:

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

3.5 NonelessDict

3.5.1 About

NonelessDict is a wrapper around dict that will check if a value is *None*/empty/*False*, and not add the key in that case.

The class has a method `set_with_strict_none_check()` that can be used to set a value and check only for *None* values.

NonelessOrderedDict is based on *NonelessDict* and *OrderedDict*, so the order of key insertion is preserved.

3.5.2 API Reference

Provides `NonelessDict`.

Classes:

<code>NonelessDict(*args, **kwargs)</code>	A wrapper around dict that will check if a value is <code>None/empty/False</code> , and not add the key in that case.
<code>NonelessOrderedDict(*args, **kwargs)</code>	A wrapper around <code>OrderedDict</code> that will check if a value is <code>None/empty/False</code> , and not add the key in that case.

class `NonelessDict` (**args, **kwargs*)

Bases: `cawdrey.base.MutableBase`

A wrapper around dict that will check if a value is `None/empty/False`, and not add the key in that case.

Use the `set_with_strict_none_check()` method to check only for `None`.

Methods:

<code>__contains__(key)</code>	Return key in self.
<code>__eq__(other)</code>	Return self == other.
<code>__getitem__(key)</code>	Return self[key].
<code>__iter__()</code>	Iterates over the dictionary's keys
<code>__len__()</code>	Returns the number of keys in the dictionary.
<code>__repr__()</code>	Return a string representation of the <code>DictWrapper</code> .
<code>clear()</code>	
<code>fromkeys(iterable[, value])</code>	Create a new dictionary with keys from iterable and values set to value.
<code>get(k[, default])</code>	Return the value for k if k is in the dictionary, else default.
<code>items()</code>	Returns a set-like object providing a view on the <code>bdict</code> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <code>bdict</code> 's keys.
<code>pop(k[,d])</code>	If key is not found, d is returned if given, otherwise <code>KeyError</code> is raised.
<code>popitem()</code>	as a 2-tuple; but raise <code>KeyError</code> if D is empty.
<code>set_with_strict_none_check(key, value)</code>	
	param key
<code>setdefault(k[,d])</code>	
<code>update([E,]**F)</code>	If E present and has a <code>.keys()</code> method, does: for k in E: D[k] = E[k] If E present and lacks <code>.keys()</code> method, does: for (k, v) in E: D[k] = v In either case, this is followed by: for k, v in F.items(): D[k] = v
<code>values()</code>	Returns an object providing a view on the <code>bdict</code> 's values.

`__contains__(key)`

Return key in self.

Parameters `key` (object)

Return type `bool`

`__eq__` (*other*)

Return `self == other`.

Return type `bool`

`__getitem__` (*key*)

Return `self[key]`.

Parameters **key** (~KT)

Return type ~VT

`__iter__` ()

Iterates over the dictionary's keys

Return type `Iterator[~KT]`

`__len__` ()

Returns the number of keys in the dictionary.

Return type `int`

`__repr__` ()

Return a string representation of the `DictWrapper`.

Return type `str`

`clear` () → None. Remove all items from D.

classmethod `fromkeys` (*iterable*, *value=None*)

Create a new dictionary with keys from *iterable* and values set to *value*.

`get` (*k*, *default=None*)

Return the value for *k* if *k* is in the dictionary, else *default*.

Parameters

- **k** – The key to return the value for.
- **default** – The value to return if *key* is not in the dictionary. Default `None`.

`items` ()

Returns a set-like object providing a view on the `bdict`'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

`keys` ()

Returns a set-like object providing a view on the `bdict`'s keys.

Return type `AbstractSet[~KT]`

`pop` (*k*, [*d*]) → *v*, remove specified key and return the corresponding value.

If *key* is not found, *d* is returned if given, otherwise `KeyError` is raised.

`popitem` () → (*k*, *v*), remove and return some (key, value) pair

as a 2-tuple; but raise `KeyError` if D is empty.

`set_with_strict_none_check` (*key*, *value*)

Parameters

- **key**
- **value**

Return type `None`

setdefault (k , d) → $D.get(k,d)$, also set $D[k]=d$ if k not in D

update ($[E]$, $**F$) → $None$. Update D from mapping/iterable E and F .

If E present and has a `.keys()` method, does: for k in E : $D[k] = E[k]$ If E present and lacks `.keys()` method, does: for (k, v) in E : $D[k] = v$ In either case, this is followed by: for k, v in $F.items()$: $D[k] = v$

values ()

Returns an object providing a view on the *bdict*'s values.

Return type `ValuesView[~VT]`

class NonelessOrderedDict ($*args$, $**kws$)

Bases: `cawdrey.base.MutableBase`

A wrapper around `OrderedDict` that will check if a value is `None/empty/False`, and not add the key in that case. Use the `set_with_strict_none_check` function to check only for `None`

Methods:

<code>__contains__(key)</code>	Return key in self.
<code>__eq__(other)</code>	Return self == other.
<code>__getitem__(key)</code>	Return self[key].
<code>__iter__()</code>	Iterates over the dictionary's keys
<code>__len__()</code>	Returns the number of keys in the dictionary.
<code>__repr__()</code>	Return a string representation of the <i>DictWrapper</i> .
<code>clear()</code>	
<code>fromkeys(iterable[, value])</code>	Create a new dictionary with keys from iterable and values set to value.
<code>get(k[, default])</code>	Return the value for k if k is in the dictionary, else default.
<code>items()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's keys.
<code>pop(k[,d])</code>	If key is not found, d is returned if given, otherwise <code>KeyError</code> is raised.
<code>popitem()</code>	as a 2-tuple; but raise <code>KeyError</code> if D is empty.
<code>setdefault(k[,d])</code>	
<code>update([E,]**F)</code>	If E present and has a <code>.keys()</code> method, does: for k in E : $D[k] = E[k]$ If E present and lacks <code>.keys()</code> method, does: for (k, v) in E : $D[k] = v$ In either case, this is followed by: for k, v in $F.items()$: $D[k] = v$
<code>values()</code>	Returns an object providing a view on the <i>bdict</i> 's values.

`__contains__` (key)

Return key in self.

Parameters `key` (object)

Return type `bool`

`__eq__` ($other$)

Return self == other.

Return type `bool`

`__getitem__` (*key*)
Return `self[key]`.

Parameters **key** (~KT)

Return type ~VT

`__iter__` ()
Iterates over the dictionary's keys

Return type `Iterator[~KT]`

`__len__` ()
Returns the number of keys in the dictionary.

Return type `int`

`__repr__` ()
Return a string representation of the `DictWrapper`.

Return type `str`

`clear` () → None. Remove all items from D.

`classmethod fromkeys` (*iterable, value=None*)
Create a new dictionary with keys from *iterable* and values set to *value*.

`get` (*k, default=None*)
Return the value for *k* if *k* is in the dictionary, else *default*.

Parameters

- **k** – The key to return the value for.
- **default** – The value to return if *key* is not in the dictionary. Default `None`.

`items` ()
Returns a set-like object providing a view on the `bdict`'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

`keys` ()
Returns a set-like object providing a view on the `bdict`'s keys.

Return type `AbstractSet[~KT]`

`pop` (*k*, [*d*]) → *v*, remove specified key and return the corresponding value.
If *key* is not found, *d* is returned if given, otherwise `KeyError` is raised.

`popitem` () → (*k*, *v*), remove and return some (key, value) pair
as a 2-tuple; but raise `KeyError` if D is empty.

`setdefault` (*k*, [*d*]) → `D.get(k,d)`, also set `D[k]=d` if *k* not in D

`update` (*[E]*, ***F*) → None. Update D from mapping/iterable E and F.
If E present and has a `.keys()` method, does: for *k* in E: `D[k] = E[k]` If E present and lacks `.keys()` method,
does: for (*k*, *v*) in E: `D[k] = v` In either case, this is followed by: for *k*, *v* in `F.items()`: `D[k] = v`

`values` ()
Returns an object providing a view on the `bdict`'s values.

Return type `ValuesView[~VT]`

3.5.3 Copyright

Based on <https://github.com/slezica/python-frozendict> and <https://github.com/jerr0328/python-helpfuldicts> .

Copyright (c) 2012 Santiago Lezica

Licensed under the MIT License:

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

3.6 Base Classes

3.6.1 About

FrozenBase is the base class for *frozendict* and *FrozenOrderedDict*. If you wish to construct your own frozen dictionary classes, you may inherit from this class.

3.6.2 API Reference

Base Classes

Classes:

<i>DictWrapper</i> (*args, **kwargs)	Abstract Mixin class for classes that wrap a dict object or similar
<i>FrozenBase</i> (*args, **kwargs)	Abstract Base Class for Frozen dictionaries
<i>MutableBase</i> (*args, **kwargs)	Abstract Base Class for mutable dictionaries

class DictWrapper (*args, **kwargs)

Bases: `collections.abc.Mapping`, `typing.Generic`

Abstract Mixin class for classes that wrap a dict object or similar

Methods:

<code>__contains__(key)</code>	Return key in self.
<code>__eq__(other)</code>	Return self == other.
<code>__getitem__(key)</code>	Return self[key].
<code>__iter__()</code>	Iterates over the dictionary’s keys

continues on next page

Table 9 – continued from previous page

<code>__len__()</code>	Returns the number of keys in the dictionary.
<code>__repr__()</code>	Return a string representation of the <i>DictWrapper</i> .
<code>get()</code>	Return the value for <i>k</i> if <i>k</i> is in the dictionary, else default.
<code>items()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's keys.
<code>values()</code>	Returns an object providing a view on the <i>bdict</i> 's values.

`__contains__(key)`

Return *key* in *self*.

Parameters *key* (object)

Return type `bool`

`__eq__(other)`

Return *self* == *other*.

Return type `bool`

`__getitem__(key)`

Return *self*[*key*].

Parameters *key* (~KT)

Return type ~VT

`__iter__()`

Iterates over the dictionary's keys

Return type `Iterator[~KT]`

`__len__()`

Returns the number of keys in the dictionary.

Return type `int`

`__repr__()`

Return a string representation of the *DictWrapper*.

Return type `str`

`get(k: KT) → Optional[VT]`

`get(k: KT, default: Union[VT, T]) → Union[VT, T]`

Return the value for *k* if *k* is in the dictionary, else default.

Parameters

- **k** – The key to return the value for.
- **default** – The value to return if *key* is not in the dictionary. Default `None`.

`items()`

Returns a set-like object providing a view on the *bdict*'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

`keys()`

Returns a set-like object providing a view on the *bdict*'s keys.

Return type `AbstractSet[~KT]`

values ()

Returns an object providing a view on the *bdict*'s values.

Return type `ValuesView[~VT]`

class FrozenBase (*args, **kws)

Bases: `cawdrey.base.DictWrapper`

Abstract Base Class for Frozen dictionaries

Used by `frozendict` and `FrozenOrderedDict`.

Custom subclasses must implement at a minimum `__init__`, `copy`, `fromkeys`.

Methods:

<code>__contains__(key)</code>	Return key in self.
<code>__eq__(other)</code>	Return self == other.
<code>__getitem__(key)</code>	Return self[key].
<code>__iter__()</code>	Iterates over the dictionary's keys
<code>__len__()</code>	Returns the number of keys in the dictionary.
<code>__repr__()</code>	Return a string representation of the <i>DictWrapper</i> .
<code>fromkeys()</code>	Create a new dictionary with keys from iterable and values set to value.
<code>get(k[, default])</code>	Return the value for k if k is in the dictionary, else default.
<code>items()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <i>bdict</i> 's keys.
<code>values()</code>	Returns an object providing a view on the <i>bdict</i> 's values.

`__contains__(key)`

Return key in self.

Parameters `key` (object)

Return type `bool`

`__eq__(other)`

Return self == other.

Return type `bool`

`__getitem__(key)`

Return self[key].

Parameters `key` (~KT)

Return type ~VT

`__iter__()`

Iterates over the dictionary's keys

Return type `Iterator[~KT]`

`__len__()`

Returns the number of keys in the dictionary.

Return type `int`

`__repr__()`

Return a string representation of the *DictWrapper*.

Return type `str`

classmethod `fromkeys` (*iterable: Iterable[_T]*) → *FrozenBase*[_T, Any]

classmethod `fromkeys` (*iterable: Iterable[_T], value: _S*) → *FrozenBase*[_T, _S]

Create a new dictionary with keys from iterable and values set to value.

get (*k, default=None*)

Return the value for *k* if *k* is in the dictionary, else default.

Parameters

- **k** – The key to return the value for.
- **default** – The value to return if *key* is not in the dictionary. Default `None`.

items ()

Returns a set-like object providing a view on the *bdict*'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

keys ()

Returns a set-like object providing a view on the *bdict*'s keys.

Return type `AbstractSet[~KT]`

values ()

Returns an object providing a view on the *bdict*'s values.

Return type `ValuesView[~VT]`

class `MutableBase` (*args, **kws)

Bases: `cawdrey.base.DictWrapper`, `collections.abc.MutableMapping`, `typing.Generic`

Abstract Base Class for mutable dictionaries

Used by *NonelessDict* and *NonelessOrderedDict*.

Custom subclasses must implement at a minimum `__init__`, `copy`, `fromkeys`.

Methods:

<code>__contains__(key)</code>	Return <i>key</i> in <i>self</i> .
<code>__eq__(other)</code>	Return <i>self</i> == <i>other</i> .
<code>__getitem__(key)</code>	Return <i>self</i> [<i>key</i>].
<code>__iter__()</code>	Iterates over the dictionary's keys
<code>__len__()</code>	Returns the number of keys in the dictionary.
<code>__repr__()</code>	Return a string representation of the <i>DictWrapper</i> .
<code>clear()</code>	
<code>fromkeys()</code>	Create a new dictionary with keys from iterable and values set to value.
<code>get(k[, default])</code>	Return the value for <i>k</i> if <i>k</i> is in the dictionary, else default.

continues on next page

Table 11 – continued from previous page

<code>items()</code>	Returns a set-like object providing a view on the <code>bdict</code> 's items.
<code>keys()</code>	Returns a set-like object providing a view on the <code>bdict</code> 's keys.
<code>pop(k[,d])</code>	If key is not found, d is returned if given, otherwise <code>KeyError</code> is raised.
<code>popitem()</code>	as a 2-tuple; but raise <code>KeyError</code> if D is empty.
<code>setdefault(k[,d])</code>	
<code>update([E,]**F)</code>	If E present and has a <code>.keys()</code> method, does: for k in E: D[k] = E[k] If E present and lacks <code>.keys()</code> method, does: for (k, v) in E: D[k] = v In either case, this is followed by: for k, v in F.items(): D[k] = v
<code>values()</code>	Returns an object providing a view on the <code>bdict</code> 's values.

`__contains__` (*key*)

Return key in self.

Parameters `key` (object)

Return type `bool`

`__eq__` (*other*)

Return self == other.

Return type `bool`

`__getitem__` (*key*)

Return self[key].

Parameters `key` (~KT)

Return type ~VT

`__iter__` ()

Iterates over the dictionary's keys

Return type `Iterator[~KT]`

`__len__` ()

Returns the number of keys in the dictionary.

Return type `int`

`__repr__` ()

Return a string representation of the `DictWrapper`.

Return type `str`

`clear` () → None. Remove all items from D.

classmethod `fromkeys` (*iterable: Iterable[_T]*) → `MutableBase[_T, Any]`

classmethod `fromkeys` (*iterable: Iterable[_T], value: _S*) → `MutableBase[_T, _S]`

Create a new dictionary with keys from `iterable` and values set to `value`.

`get` (*k, default=None*)

Return the value for k if k is in the dictionary, else `default`.

Parameters

- `k` – The key to return the value for.

- **default** – The value to return if `key` is not in the dictionary. Default `None`.

items ()

Returns a set-like object providing a view on the `bdict`'s items.

Return type `AbstractSet[Tuple[~KT, ~VT]]`

keys ()

Returns a set-like object providing a view on the `bdict`'s keys.

Return type `AbstractSet[~KT]`

pop (`k`, `d`) → `v`, remove specified key and return the corresponding value.

If key is not found, `d` is returned if given, otherwise `KeyError` is raised.

popitem () → (`k`, `v`), remove and return some (key, value) pair

as a 2-tuple; but raise `KeyError` if `D` is empty.

setdefault (`k`, `d`) → `D.get(k,d)`, also set `D[k]=d` if `k` not in `D`

update (`[E]`, `**F`) → `None`. Update `D` from mapping/iterable `E` and `F`.

If `E` present and has a `.keys()` method, does: for `k` in `E`: `D[k] = E[k]` If `E` present and lacks `.keys()` method, does: for (`k`, `v`) in `E`: `D[k] = v` In either case, this is followed by: for `k`, `v` in `F.items()`: `D[k] = v`

values ()

Returns an object providing a view on the `bdict`'s values.

Return type `ValuesView[~VT]`

3.7 Functions

alphabetical_dict (`**kwargs`)

Returns an `OrderedDict` with the keys sorted alphabetically.

Parameters `kwargs`

Returns

Return type

3.8 Overview

Cawdrey uses `tox` to automate testing and packaging, and `pre-commit` to maintain code quality.

Install `pre-commit` with `pip` and install the git hook:

```
$ python -m pip install pre-commit
$ pre-commit install
```

3.9 Coding style

`Yapf` is used for code formatting, and `isort` is used to sort imports.

`yapf` and `isort` can be run manually via `pre-commit`:

```
$ pre-commit run yapf -a
$ pre-commit run isort -a
```

The complete autoformatting suite can be run with `pre-commit`:

```
$ pre-commit run -a
```

3.10 Automated tests

Tests are run with `tox` and `pytest`. To run tests for a specific Python version, such as Python 3.6, run:

```
$ tox -e py36
```

To run tests for all Python versions, simply run:

```
$ tox
```

3.11 Type Annotations

Type annotations are checked using `mypy`. Run `mypy` using `tox`:

```
$ tox -e mypy
```

3.12 Build documentation locally

The documentation is powered by `Sphinx`. A local copy of the documentation can be built with `tox`:

```
$ tox -e docs
```

3.13 Downloading source code

The `Cawdrey` source code is available on GitHub, and can be accessed from the following URL: <https://github.com/domdfcoding/cawdrey>

If you have `git` installed, you can clone the repository with the following command:

```
$ git clone https://github.com/domdfcoding/cawdrey"
> Cloning into 'cawdrey'...
> remote: Enumerating objects: 47, done.
> remote: Counting objects: 100% (47/47), done.
> remote: Compressing objects: 100% (41/41), done.
> remote: Total 173 (delta 16), reused 17 (delta 6), pack-reused 126
> Receiving objects: 100% (173/173), 126.56 KiB | 678.00 KiB/s, done.
> Resolving deltas: 100% (66/66), done.
```

Alternatively, the code can be downloaded in a ‘zip’ file by clicking:

Clone or download → *Download Zip*




Fig. 1: Downloading a 'zip' file of the source code

3.13.1 Building from source

The recommended way to build Cawdrey is to use `tox`:

```
$ tox -e build
```

The source and wheel distributions will be in the directory `dist`.

If you wish, you may also use `pep517.build` or another **PEP 517**-compatible build tool.

View the [Function Index](#) or browse the [Source Code](#).

[Browse the GitHub Repository](#)

AND FINALLY:

Why “Cawdrey”?

PYTHON MODULE INDEX

C

`cawdrey.base`, 24

`cawdrey.nonelessdict`, 20

Symbols

__add__() (*frozendict method*), 14
 __and__() (*frozendict method*), 14
 __contains__() (*AlphaDict method*), 8
 __contains__() (*DictWrapper method*), 25
 __contains__() (*FrozenBase method*), 26
 __contains__() (*FrozenOrderedDict method*), 17
 __contains__() (*MutableBase method*), 28
 __contains__() (*NonelessDict method*), 20
 __contains__() (*NonelessOrderedDict method*), 22
 __contains__() (*bdict method*), 10
 __contains__() (*frozendict method*), 14
 __delitem__() (*bdict method*), 10
 __eq__() (*AlphaDict method*), 8
 __eq__() (*DictWrapper method*), 25
 __eq__() (*FrozenBase method*), 26
 __eq__() (*FrozenOrderedDict method*), 17
 __eq__() (*MutableBase method*), 28
 __eq__() (*NonelessDict method*), 21
 __eq__() (*NonelessOrderedDict method*), 22
 __eq__() (*bdict method*), 10
 __eq__() (*frozendict method*), 14
 __getitem__() (*AlphaDict method*), 8
 __getitem__() (*DictWrapper method*), 25
 __getitem__() (*FrozenBase method*), 26
 __getitem__() (*FrozenOrderedDict method*), 17
 __getitem__() (*MutableBase method*), 28
 __getitem__() (*NonelessDict method*), 21
 __getitem__() (*NonelessOrderedDict method*), 22
 __getitem__() (*bdict method*), 10
 __getitem__() (*frozendict method*), 14
 __iter__() (*AlphaDict method*), 8
 __iter__() (*DictWrapper method*), 25
 __iter__() (*FrozenBase method*), 26
 __iter__() (*FrozenOrderedDict method*), 17
 __iter__() (*MutableBase method*), 28
 __iter__() (*NonelessDict method*), 21
 __iter__() (*NonelessOrderedDict method*), 23
 __iter__() (*frozendict method*), 15
 __len__() (*AlphaDict method*), 8
 __len__() (*DictWrapper method*), 25
 __len__() (*FrozenBase method*), 26

__len__() (*FrozenOrderedDict method*), 17
 __len__() (*MutableBase method*), 28
 __len__() (*NonelessDict method*), 21
 __len__() (*NonelessOrderedDict method*), 23
 __len__() (*frozendict method*), 15
 __repr__() (*AlphaDict method*), 8
 __repr__() (*DictWrapper method*), 25
 __repr__() (*FrozenBase method*), 27
 __repr__() (*FrozenOrderedDict method*), 18
 __repr__() (*MutableBase method*), 28
 __repr__() (*NonelessDict method*), 21
 __repr__() (*NonelessOrderedDict method*), 23
 __repr__() (*bdict method*), 10
 __repr__() (*frozendict method*), 15
 __setitem__() (*bdict method*), 10
 __sub__() (*frozendict method*), 15

A

alphabetical_dict() (in module *cawdrey.alphadict*), 29
 AlphaDict (class in *cawdrey*), 7

B

bdict (class in *cawdrey*), 9

C

cawdrey.base
 module, 24
 cawdrey.nonelessdict
 module, 20
 clear() (*bdict method*), 11
 clear() (*MutableBase method*), 28
 clear() (*NonelessDict method*), 21
 clear() (*NonelessOrderedDict method*), 23
 copy() (*AlphaDict method*), 8
 copy() (*FrozenOrderedDict method*), 18

D

DictWrapper (class in *cawdrey.base*), 24

F

fromkeys() (*AlphaDict class method*), 9

`fromkeys()` (*FrozenBase class method*), 27
`fromkeys()` (*frozendict class method*), 15
`fromkeys()` (*FrozenOrderedDict class method*), 18
`fromkeys()` (*MutableBase class method*), 28
`fromkeys()` (*NonelessDict class method*), 21
`fromkeys()` (*NonelessOrderedDict class method*), 23
`FrozenBase` (*class in cawdrey.base*), 26
`frozendict` (*class in cawdrey*), 13
`FrozenOrderedDict` (*class in cawdrey*), 17

G

`get()` (*AlphaDict method*), 9
`get()` (*bdict method*), 11
`get()` (*DictWrapper method*), 25
`get()` (*FrozenBase method*), 27
`get()` (*frozendict method*), 15
`get()` (*FrozenOrderedDict method*), 18
`get()` (*MutableBase method*), 28
`get()` (*NonelessDict method*), 21
`get()` (*NonelessOrderedDict method*), 23

I

`items()` (*AlphaDict method*), 9
`items()` (*bdict method*), 11
`items()` (*DictWrapper method*), 25
`items()` (*FrozenBase method*), 27
`items()` (*frozendict method*), 15
`items()` (*FrozenOrderedDict method*), 18
`items()` (*MutableBase method*), 29
`items()` (*NonelessDict method*), 21
`items()` (*NonelessOrderedDict method*), 23

K

`keys()` (*AlphaDict method*), 9
`keys()` (*bdict method*), 11
`keys()` (*DictWrapper method*), 25
`keys()` (*FrozenBase method*), 27
`keys()` (*frozendict method*), 15
`keys()` (*FrozenOrderedDict method*), 18
`keys()` (*MutableBase method*), 29
`keys()` (*NonelessDict method*), 21
`keys()` (*NonelessOrderedDict method*), 23

M

module
 cawdrey.base, 24
 cawdrey.nonelessdict, 20
`MutableBase` (*class in cawdrey.base*), 27

N

`NonelessDict` (*class in cawdrey.nonelessdict*), 20
`NonelessOrderedDict` (*class in cawdrey.nonelessdict*), 22

P

`pop()` (*bdict method*), 11
`pop()` (*MutableBase method*), 29
`pop()` (*NonelessDict method*), 21
`pop()` (*NonelessOrderedDict method*), 23
`popitem()` (*bdict method*), 11
`popitem()` (*MutableBase method*), 29
`popitem()` (*NonelessDict method*), 21
`popitem()` (*NonelessOrderedDict method*), 23
Python Enhancement Proposals
 PEP 517, 31

S

`set_with_strict_none_check()` (*NonelessDict method*), 21
`setdefault()` (*bdict method*), 11
`setdefault()` (*MutableBase method*), 29
`setdefault()` (*NonelessDict method*), 21
`setdefault()` (*NonelessOrderedDict method*), 23
`sorted()` (*frozendict method*), 15

U

`update()` (*bdict method*), 11
`update()` (*MutableBase method*), 29
`update()` (*NonelessDict method*), 22
`update()` (*NonelessOrderedDict method*), 23

V

`values()` (*AlphaDict method*), 9
`values()` (*bdict method*), 11
`values()` (*DictWrapper method*), 26
`values()` (*FrozenBase method*), 27
`values()` (*frozendict method*), 15
`values()` (*FrozenOrderedDict method*), 18
`values()` (*MutableBase method*), 29
`values()` (*NonelessDict method*), 22
`values()` (*NonelessOrderedDict method*), 23